

**SteelFiber**  
STEEL FIBER COMPOSITE

SteelFiber Hybrid Shaft Models and Specs:

SHAFT	FLEX	LENGTH	WEIGHT	TORQUE	TIP OD	BUTT OD	PARALLEL TIP	BEND POINT
SteelFiber hfs75	Stiff	44"	72gr	3.6	.335"	.600"	4.1"	Mid
SteelFiber hfs75	Regular	44"	72gr	3.8	.335"	.600"	4.1"	Mid
SteelFiber hls75	Stiff	42"	80gr	3.0	.370"	.604"	3.9"	Mid
SteelFiber hls75	Regular	42"	78gr	3.3	.370"	.600"	3.9"	Mid

SteelFiber Hybrid Tip Trimming Instructions:

Playing Length	SteelFiber hfs75	SteelFiber hls75
41" or longer	Butt trim only	Butt trim only
40.75"- 40.25"	.5"	.5"
40.00"- 39.50"	1.0"	1.0"
39.25"- 38.75"	1.5"	1.5"
38.50"- 38.00"	2.0"	2.0"
37.75" or less	2.5"	2.5"

\*Tip trim can be adjusted to fine tune playing characteristics.

\*Tip trim should not exceed (Parallel Tip - Hosel Depth).

\*Perform tip trim and then butt trim to final playing length.