

**SteelFiber**  
STEEL FIBER COMPOSITE

SteelFiber Wood Shaft Models and Specs:

SHAFT	FLEX	LENGTH	WEIGHT	TORQUE	TIP OD	BUTT OD	PARALLEL TIP	BEND POINT
SteelFiber ss65	Stiff	46"	66gr	4.3	.335"	.602"	3.5"	Mid
SteelFiber ss65	Regular	46"	66gr	4.6	.335"	.602"	3.5"	Mid
SteelFiber ss65	Senior	46"	65gr	4.6	.335"	.602"	3.5"	Mid
SteelFiber ss65 (.350")	X-Stiff	46"	67gr	3.9	.350"	.600"	3.5"	Mid
SteelFiber ss65 (.350")	Stiff	46"	64gr	4.3	.350"	.600"	3.5"	Mid
SteelFiber ss65 (.350")	Regular	46"	64gr	4.3	.350"	.600"	3.5"	Mid
SteelFiber ss75	X-Stiff	46"	78gr	3.8	.335"	.608"	4.5"	Mid
SteelFiber ss75	Stiff	46"	75gr	3.8	.335"	.600"	5.0"	Mid
SteelFiber ss75	Regular	46"	75gr	4.0	.335"	.600"	5.0"	Mid
SteelFiber ss75	Senior	46"	74gr	4.2	.335"	.600"	5.0"	Mid
SteelFiber ss75	Ladies	46"	73gr	4.2	.335"	.580"	5.0"	MidLow
SteelFiber ss75 (.350")	X-Stiff	46"	78gr	3.4	.350"	.600"	4.0"	Mid
SteelFiber ss75 (.350")	Stiff	46"	75gr	3.6	.350"	.598"	4.0"	Mid
SteelFiber ss75 (.350")	Regular	46"	75gr	3.7	.350"	.598"	4.0"	Mid
SteelFiber ss85	XX-Stiff	46"	88gr	2.9	.335"	.605"	3.5"	HighDMid
SteelFiber ss85	X-Stiff	46"	86gr	3.2	.335"	.605"	3.5"	HighDMid
SteelFiber ss85	Stiff	46"	85gr	3.3	.335"	.600"	3.5"	Mid
SteelFiber ss85	Regular	46"	84gr	3.5	.335"	.600"	3.5"	Mid
SteelFiber ss85 (.350")	X-Stiff	46"	88gr	3.0	.350"	.605"	4.3"	HighDMid
SteelFiber ss85 (.350")	Stiff	46"	86gr	3.2	.350"	.600"	4.3"	HighDMid
SteelFiber ss85 (.350")	Regular	46"	86gr	3.2	.350"	.600"	4.3"	Mid

SteelFiber Wood Shaft Tip Trimming Instructions:

SHAFT	DRIVER	3W*	5W*	7W*	9W*
SteelFiber ss65	Butt trim only	1.0"	1.5"	2.0"	2.25"
SteelFiber ss75	Butt trim only	1.0"	1.5"	2.0"	2.5"
SteelFiber ss85	Butt trim only	1.0"	1.5"	2.0"	2.25"

\*Tip trim can be adjusted to fine tune playing characteristics.

\*Tip trim should not exceed (Parallel Tip - Hosel Depth).

\*Perform tip trim and then butt trim to final playing length.